pemih	Orderguide Panthera U3 Ligh	t Y-front High - extend		e to the desktop it from there.	rt.nr. guide-U3-light-Y-front-hog-eng rev.2022-03
Adjusted by:		Tel:		Total weigh	nt (g): 0
E-mail: Adjusted for:		Date:		The weight changes	based on the choices made below.
U3 light Y-front High L. L placeing the backrest in t	as a rigid rear axle. To find a balance that suits you, there are two ve is more easy balanced and easier to drive on the rear wheels. You hree different position . U3 Light Y-front High has a seat angle of 4 49 cm in front and 47 cm at the rear without cushion. tg for seatwidth 33-45.	can tune the balance by	Blue, underlined	op" and open it with Adobe thair by clicking in the circ it ext is clickable to show in eatwidth, HH= backrest hei	l es in this guide. info or image.
	Original design	Alternative option	ons	Other option	info
	1) Chassis-colour Click on the link to see up-to-date colours. Fill in art.no. in the square				
	2) Seat width (BB) art.no. 33 cm 36 cm 36 cm L Clear	○ 39 cm ○ 39 cm L	◯ 42 cm ◯ 42 cm L		t.no include: chassis, seat, calf strap, and seat bag
	3) Seat depth art.no. ○ Clear			○ 37,5 cm	○ 42,5 cm
	4) Back rest	Tapered 525BBHH L Curved backd 524BBHH L Upholstery, comfort U3 Light backrest with and stronger ribbons the	3 upholstery - more padding	Backrest, exten	backrest systems
ABC	5) <u>Balance</u> center of gravity (COG) Position A Least easy balanced Clear	Position C	The positioning of the ba of the wheelchair. "easy b This o		tice rear wheel balance.
	6) Castor and fork 90 mm X art.no. Clear	90 mm S3 art.no. 120 mm S3 art.no.			
	7) Footrest info about footrest height Footrest X 36004BB	Footrest Titanium 36915BB Extended, reinfo 36006BB needed for F Plastic plate for f 36010BB	rced reewheel	Other footre	est
in.	8) Brake One arm brake, right art.no. Clear	Brake \$3 4630000		One arm bra	ike, left
	9) Rear wheel - without pushrim art.no. 24" Spinergy X white spokes 24" Spinergy X black spokes Clear	25" Spinergy X whit 25" Spinergy X blac 26" Spinergy X whit 26" Spinergy X blac	k spokes te spokes	Other rear w	rheel
	Tire - choose tire Schwalbe One 24", 25" Clear	Right Run 24", 25 Marathon Plus 2-		Rugged 24" reTyre-tyre sk	ins
					side 1/2

10) Pushrim Aluminum X 24" 1904404 (x2) Aluminum X 25" 1904405 (x2) Aluminum X 26" 1904406 (x2) Clear	0	Titanium 190DD11 x2 Paragrip 19051DDBT x2 Tetragrip 19052DDBT x2 DD = Whe	laxgrip 24" (contains latex) 103060 x2
Accessories			
Side guard * Carbon, without cover art.no. * Choose 26" sideguards and arm support when 24" reawheels are mounted Clear		Side guard * Carbon,small cover art.no. Carbon, large cover* art.no. *Only with one arm brake Side guard S3 art.no.	Arm support * Arm support S3 Video art.no. Makes the wheelchair 15mm wider
Cushion Seat depth 35cm Seat depth 40cm ○ 2,5 cm 572BB35 575BB35 5 cm 575BB40 575BB40 Clear 575BB40		4245000	Seat bag Included in the prize. Choose model. Seat mounted 9900212 Cushion mounted 9900213 Clear
Wedge cushion Wedge cushion 57710BB		Other Tube protection 9900251 (x3/wheelchair) Backrest wedge 4710012 Chose art.no. for Freewheel accord the wheelchair Read more about F	

Set-up adjustments



Back rest angle

Note measure (A) for desired back rest angle. 10-20 mm. Standard=18 mm

A=____ mm



Freewheel Height 6-14 cm art.no. 2600102

Footrest height info about footrest height

Note measure (A) for desired footrest height.

A=____ mm

Extra